

T3

For excavators 1.5-4.0 ton



HYDRAULIC MULCHERS

T3 70

T3 90



HF2

Ø max 5 cm

standard equipment



H1C


Ø max 4 cm



KC1

Ø max 3 cm



Model	 (ton)	 (cm)	 (LxAxH cm)	 Kg	Motor displacement	 (L/min)	 bar (min-max)	Transmission	Rotor	
T3 70	1.5-4.0	70	95x55x45	130	8-11-16	20-30-40	170-220	direct	helical	10
T3 90	2.0-4.0	90	115x55x45	150	11-16	30-40	170-220	direct	helical	14

TECHNICAL FEATURES AND STANDARD EQUIPMENT

- Direct transmission.
- Internally reinforced with double metal sheet.
- Feeler roller adjustable on 3 positions to change the height of the cut.
- Helicoidal rotor with austempered hammers or blade interchangeable.
- Protective cover for motor.
- Inside rotor supports with labyrinth for the protection of the bearings by the impurities.
- Double row spherical adjustable bearings of 1st quality.
- Valves block complete with priority valve for adjusting oil flow, anti-shock valve (pressure relief valve), anti-cavitation.
- Gear motor.
- Accident prevention rubber protections according to EC directives.

ACCESSORIES

- 1 - Mounting hitch & pins.
- 2 - Kit hoses Lg. 2 meters.
- 3 - Front chain protection.
- 4 - Self-levelling support (+30kg).
- 5 - Valves block deduction, only anticavitation.



1



3



4